ARC SERIES 600X1200MM






COLOR SHADES

OTHER

COLOR SHADES

South India Tiles symbolizes the evolution of porcelain and ceramic tiles, focusing on the luxury segment in their collections. We pride ourselves on having extensive working knowledge of both industry standards and design trends. Our showroom features a curated selection of the highest quality products from around the nation, which we pair with complimentary design services by highly trained and professional interior designers. Our goal is to elevate your space and provide a thoughtful, personalized experience


Under one dach, we offer a wide range of brands. In our carefully designed shop atmosphere, we promise to offer you the newest designs and fits for tiles. The product range available at our studios involves all of the senses thereby allowing the user to enjoy personal spaces that offer a new sense of well-being. Our inspiration abounds. Choose among thousands of patterns inspired by nature. Choose the wood, marble, antique, textured, natural, modern, and more from numerous looks. Choose from glazed to glossed, matte to rustic, and many more tile finishes. Welcome again, to the world of innovation!





INSPIRATION

Inspiring from the color shades of natural beauty we are designing something marvelous that give your quality ambiance to meaningful classic and contemporary combination of look and create that Symbolizes Simplicity of Comfort for your space.



INNOVATION

We are serving Glorious abstractness of design innovation to create extraordinary feel for every wall space and make them more graceful with our luxury wall tiles and create aesthetic perfect context that suited to various styles of interior.

APPLIGATION

We are presenting the natural finest of result for your quality spaces and make them more graceful. We are offering different tiles with rang of colors, textures and designs and size that is fit for your every space.



Home indoor flooring and wall cladding



Elevation



Commercial & public are



Industrial areas



Hospita



Gardens and public areas



Office, shop & boutique building



Big project

GOLOR



SIZE 600X1200MM

SURFACE MATT

THICKNESS 9MM



SIZE 600X1200MM | SURFACE MATT





SPLIT LIGHT GREY

4 Phase



Application




SIZE 600X1200MM | SURFACE MATT




SPLIT CREMA

4 Phase





Application




SIZE 600X1200MM | SURFACE MATT





SPLIT GREY 4 Phase



SPLIT AVALON GREY

4 Phase




Application




SIZE 600X1200MM | SURFACE MATT





SPLIT BROWN 4 Phase



SPLIT AVALON BROWN

4 Phase

Application




SIZE 600X1200MM | SURFACE MATT





SPLIT BLACK 4 Phase



SPLIT AVALON BLACK

4 Phase

Application

Technical Specification

CHARACTERISTIC	STANDARD AS PER ISO-13006/EN 14411 GROUP Bla	MEAN VALUE OF POLISHED GVT	MEAN VALUE OF RUSTIC GVT	TEST METHOD
DECLINATION PROPERTIES				
REGULATORY PROPERTIES Deviation in length & width	+0 5 0/-	±0.1 %	±0.1 %	ISO 10545 2
_	±0.5 %			ISO-10545-2
Deviation in thickness	±5.0 %	±4.0 %	±4.0 %	ISO-10545-2
itraightness in side	±0.5 %	±0.1 %	±0.1 %	ISO-10545-2
Rectangularity	±0.5 %	±0.1 %	±0.1 %	ISO-10545-2
Surface flatness	±0.5 %	±0.2 %	±0.2 %	ISO-10545-2
Color difference	Unaltered	No change	No change	ISO-10545-16
Glossiness	As per mfg	Min 90%	Min 4%	GLOSSOMETER
STRUCTURAL PROPERTIES				
Vater absorption	< 0.50 %	< 0.20 %	< 0.20 %	ISO-10545-3
Apparent density	> 2.0 g/cc	>2.10 g/cc	>2.10 g/cc	DIN 51082
AASSIVE MECHANICAL PROPE	RTIES			
Modulus of rupture	Min. 35 N/mm ²	Min. 40 N/mm ²	Min. 40 N/mm ²	ISO-10545-4
reaking strength	Min. 1300 N	Min. 2000 N	Min. 2000 N	ISO-10545-4
mpact resistance	As per mfg.	Min. 0.55	Min. 0.55	ISO-10545-5
SURFACE MECHANICAL PROPE	RTIES			
urface abrasion resistance	As per mfg.	Min. Class-3	Min. Class-4	ISO-10545-7
MOH's hardness	As per mfg.	Min. 4	Min. 5	EN 101
HERMO HYGROMETRIC PROP	EDTIES			
rost resistance	No damage	No damage	No damage	ISO-10545-12
hermal shock resistance	No damage	No damage	No damage	ISO-10545-9
Noisture expansion	Nil	Nil	Nil	ISO-10545-10
Thermal expansion (COE)	Max. 9.0 x 10 ⁻⁶	Max. 6.5x10 ⁻⁶	Max. 6.5 x 10 ⁻⁶	ISO-10545-8
Crazing resistance	As per mfg.	Min. 10 Cycle	Min. 10 Cycle	ISO-10545-0
ruzing resistance	7.5 per mig.	Will. To Cycle	Will. To Cycle	130-10343-11
HEMICAL PROPERTIES				
hemical resistance	No damage	No damage	No damage	ISO-10545-13
tain resistance	Resistant	Resistant	Resistant	ISO-10545-14
AFETY PROPERTIES				
lip resistance	As per mfg.	>0.40	>0.40	ISO-10545-17
ire resistance	As per mfg.	Fire proof	Fire proof	N. A.
ead & Cadmium given off	As per mfg.	Does not yield Pb & Cd	Does not yield Pb & Cd	ISO-10545-15

PACKING DETAILS

SR. NO	PRODUCT	NOMINAL SIZE	THICKNESS	TILES PER BOX	COVERAGE AREA
1	VITRIFIED TILES	600x1200mm	9 mm	2	1.44 Sq. Mtr.



South India Tiles 159/1, Bashyakarlu Rd east, R.S. Puram, Coimbatore Tamilnadu 641002

E-mail: info@southindiatiles.com | www.southindiatiles.com | Number: +91 7066666618