



Classic Premium Series

**8MM | AC 4 GRADE LAMINATE FLOORING
WITH WAX COATED LOCK, WITH ORIGINAL UNILIN LOCKING**

Inspire Decor Space

Size : 1210mm x 192mm

Thickness - 8mm

10 Pcs per box - 25sqft



Code : CL 1021

FLOATING CLOUD OAK

LAMINATE FLOORING IS MADE BY COATING AND LAMINATING HDF BOARDS WITH WOOD-PATTERNED PAPER.



High-qualit Eco-Friendly Flooring

- Minimum amounts of formaldehyde.



NANO Silver Ion Overlay

- It is excellent in abrasion resistance and durability, and the silver ions boost great antibacterial and insect repellent functions



Quality Assurance

- 10 Year residential warranty
- 5 Year commercial warranty



Authentic Surface texture

- Real Wood-like texture at reasonable price.



Micro Bevel

- Classy created the delicate micro bevel to add real wooden floor feel.



Edge Coating

- Provides resistance on moisture and protects from humid environment



Abrasion, Impact, Scratch Resistance, Ac4 Class

- Suitable for both residential & commercial applications.



Part Replacement

- Can be easily replaced using spare panels when damaged.



Unilin Patented Locking

- Original unilin locks with bar code stickers on boxes



Code : CL 1021

Size : 1210mm x 192mm

Thickness - 8mm

10 Pcs per box - 25sqft



Code : CL 1022



Code : CL 1022

Size : 1210mm x 192mm

Thickness - 8mm

10 Pcs per box - 25sqft



Code : CL 1023



Code : CL 1023

Size : 1210mm x 192mm

Thickness - 8mm

10 Pcs per box - 25sqft



Code : CL 1024



Code : CL 1024

Size : 1210mm x 192mm

Thickness - 8mm

10 Pcs per box - 25sqft



Code : CL 1025



Code : CL 1025

Size : 1210mm x 192mm

Thickness - 8mm

10 Pcs per box - 25sqft



Code : CL 1026

BROWN ELM



Classic Premium Series

- Awesome II patented Classic Premium Series overlay will prevent bacteria on the floor.
- Emits far-infrared radiation, which is good for human body.

Decorative layer

- Comes in the widest range of design patterns available

Eco-friendly HDF core

- Minimum amounts of formaldehyde,

The back side treatment

- Use balanced sheet for highly resistant to moisture and prevention of bending.

Tongue-in groove system

- Installed by using the exquisite unick method, which requires no adhesives.



Code : CL 1026

Size : 1210mm x 192mm

Thickness - 8mm

10 Pcs per box - 25sqft



Code : CL 1027



Code : CL 1027

Size : 1210mm x 192mm

Thickness - 8mm

10 Pcs per box - 25sqft



Code : CL 1028



Code : CL 1028

Size : 1210mm x 192mm

Thickness - 8mm

10 Pcs per box - 25sqft



Code : CL 1029



Code : CL 1029

Size : 1210mm x 192mm

Thickness - 8mm

10 Pcs per box - 25sqft



Code : CL 1030



Code : CL 1030

TECHNICAL DETAILS

Product		Dimension	Emission
Laminate Flooring		L 1210* W 192*T8	E2
Item		Test Method	Spec
Density (kg/m ³)		EN 323	850 ↑
	Length	EN 13329	+0.2
	Width	EN 13329	+0.2
Dimension	Thickness	EN 13329	+0.2
	Depth Difference	EN 13329	0.15 ↓
Moisture (%)		EN 322	5.0~8.0
MOR (N/mm ²)		EN 310	35 ↑
IB (N/mm ²)		EN 319	1.2 ↑ (min 1.0 ↑)
Edge Thickness swelling (%)		EN 13329	18↓
Abrasion Resistance	Wear Value (A C3)	EN 13329	2000↑
Scratch Resistance (N)		ISO 4586	3.5 ↑
Impact Resistance		EN 13329	I C2 for 31th class
Stain Resistance		EN 13329	None
Emission (mg/100g)		EN 120	8 ~ 30
	Fw concave	EN 13329	0.15↓
Surface	Fw concave	EN 13329	0.2↓
smoothness (%)	F1 concave	EN 13329	0.5↓
	F1 concave	EN 13329	1↓
Surface soundness (N/mm ²)		EN 13329	1 ↑

